

1. Product and Company Information

Product Series	Spherix®	
Product Use	Additive for use in rubber, plastics, composites, adhesives, coatings, and sealants	
Product Type	roduct Type Ultra-fine-grained ceramic mineral additive	
Manufacturer	Spherix Products, Two Notch Road, Lexington, SC 29073. 1-844-774-3749 customersupport@spherixproducts.com	

2. Hazards Identification

substance	
Skin irritation, Category 2. Eye irritation, Category 2B. Specific Target Organ Toxicant, Single Exposure, Category 3.	
Respirable particles may become airborne if agitated. Provide workplace air filtration engineering controls, capable of removing at least 99% of particulates. If action levels of airborne respirable silica may be exceeded over a 30-day period, use facemasks with an assigned protection factor of 50 and equipped with filter P-100 cartridges.	
Upper respiratory tract irritation Coughing Irritation of eyes and mucous membranes Skin irritation	
Danger	
◆ ◆	
Dust may cause respiratory irritation. Repeated/prolonged exposure to dust inhalation may cause damage to lungs.	
Statements	
Avoid prolonged skin contact Avoid ingestion Avoid breathing dust Use respiratory protection.	
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so. Continue rinsing. If eye irritation persists, get medical advice/attention. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER if you feel unwell. IF SKIN IRRITATION OCCURS: Get medical advice/attention.	
Store bags in dry, well-ventilated place with container tightly closed. Store locked up.	
NON-HAZARDOUS (EPA). Product does not constitute hazardous waste. Federal Register 21301-21501. April 17, 2015.	
lazards	
Avoid prolonged skin contact Avoid breathing substance Avoid ingestion Use respiratory protection Wash skin with soapy water.	

3. Composition Information

Ingredient Name	CAS Number	Wt.%	UN GHS (Rev 4) Classification	
Aluminosilicate Solid Ceramic Spheres	68131-74-8	95-99	Single Exposure STOT, Hazard Category 3	
Silica, Respirable	14808-60-7	0.2-1	Repeated exposure STOT, Hazard Category 2	
Components of Solid, Ceramic Spheres				
Amorphous Silicon Dioxide	60676-86-0	40-55		
Alumina	1344-28-1	25-35		
Iron Oxide	1309-37-1	3-12		
Calcium Oxide	1305-78-8	2-4	Spheres: Single Exposure STOT	
Potassium Oxide	12136-45-7	2-4	Hazard Category 3	
Magnesium Oxide	1309-48-4	1-2		
Titanium Oxide	13463-67-7	0.1-4		
Crystalline Silica	14808-60-7	0.1-2		

4. First Aid Measures

Inhalation	Remove person to fresh air. Dust in throat and nasal passage should clear spontaneously. Consult a physician if discomfort or difficulty breathing persists.
Eye Contact	Do not rub. Flush eyes with water for several minutes. Consult a physician if there is persistent irritation.
Skin Contact	No acute hazard is associated with short-term skin contact. Avoid prolonged skin contact. Periodic washing of skin with soap and water is recommended.
Ingestion	Rinse mouth with water; clear nose and throat. No specific first aid measures are required.
Most important health effects, both acute and delayed	Acute: irritated respiratory tract and eyes. Chronic effects: frequent inhalation of dust levels above permissible exposure limits (PEL) over a long period of time increases the risk of developing lung damage, including silicosis.



Indication of any immediate medical attention and special treatment needed

None on short term exposure to dust. Get medical attention if inhalation is severe/prolonged and respiratory symptoms persist after immediate first aid measures are given.

5. Fire-Fighting Measures

Suitable Extinguishing Media	Product is noncombustible. Use extinguishing media for surrounding materials.
Extinguishing Media Which Should Not be Used	No restriction
Special Exposure Hazards	No unusual fire or explosion hazards noted. No anticipated thermal decomposition products.
Special Protective Equipment for Fire Fighters	Wear dust mask.

6. Accidental Release Measures

Personal Precautions	No action shall be taken involving any personal risk or without suitable training. Don appropriate personal protective equipment. If ventilation is inadequate, utilize appropriate respiratory protection. Avoid airborne dust generation.
Environmental Precautions	Spherix® does NOT CONSTITUTE HAZARDOUS WASTE.
Methods of Cleaning Up	Do not dry sweep. Do not use compressed air. Water spray or HEPA equipped vacuum is recommended for removing spilled material. Minimize generation of airborne dust during cleanup activities.

7. Handling and Safe Storage

Handling		
Advice on Safe Handling	No special precautions, except for controlling dust. Dust masks equipped with N-100 HEPA filters are advised. Periodically vacuum (HEPA filter) accumulated dust on walls, floors, sills, ledges, machinery, or equipment. Keep airborne dust concentrations below PEL.	
Technical Measures and Storage Adequate exhaust ventilation should be operational in closed places whe generated. Keep containers closed.		
Storage		
Technical Measures and Storage	Containers need to be protected from physical damage that could lead to spillage and airborne dust generation.	
Packaging Materials	Keep containers closed and store bags to avoid accidental tearing, breaking, or bursting. Packaging bags can be disposed of as ordinary refuse in any sanitary landfill or by incineration.	

8. Exposure Controls/Personal Protection

Ingredient Name	OSHA PEL	ACGIH TLV	NIOSH REL
Respirable Silica (Quartz)	0.05 mg/m3 8-Hr. TWA Action level: 0.025 mg/m3 8 Hr. TWA 30 or more days per year.	0.1 mg/m3 (respirable dust)	0.05 mg/m3 10 Hr. TWA (respirable dust)
Biological Limit Values	There are no ACGIH Biolog spheres.	ical Exposure Indices (BEI®) fo	or Spherix® solid aluminosilicate
DNEL/NMEL Values	Not Available	Not Available	

DNEL/NMEL Values	Not Available
PNEC Values	Not Available
General Exposure Controls	Provide ventilation to maintain the ambient workplace atmosphere below the occupational exposure limit(s). Use general and local exhaust ventilation and dust collection systems as necessary to minimize exposure.
Eye Protection	Safety glasses or goggles are recommended.
Skin Protection	Wear gloves and work clothing that minimizes skin contact.
Environmental Exposure Controls	Contain spills and prevent wind dispersal. Follow state regulations for disposal, water emissions, and air emissions.

9. Physical and Chemical Properties

Appearance	
Physical State	Solid (powder)
Color	Beige (dry powder state)
Odor	No odor
Properties	
Flash Point	Noncombustible
Explosion Limits (Upper)	Not available



Explosion Limits (Lower)	Not available
pH (10% aqueous slurry)	6.5 - 7.5
Melting Point	Greater than 1600°F
Boiling Point	Not available
Relative Density	2.3 - 2.4
Vapor Pressure	Zero
Odor Threshold	N/A
Viscosity	N/A
Solubility (water)	Insoluble
Partition Coefficient n-octanol/water	Resides in water phase
Evaporation Rate	Zero
Vapor Density	N/A - No volatile components

10. Stability and Reactivity

Conditions to Avoid	Prolonged agitation that generates dust
Materials to Avoid	Strong acids, strong oxidizers
Chemical Stability	Chemically stable in all conditions of normal use
Possible Hazardous Reactions	Material is a stable earthen mineral. Polymerization will not occur.
Hazardous Decomposition Products	Not known

11. Toxicological Information

General Information	Spherix® as a mixture has not been evaluated for toxicological information. It is made of amorphous aluminosilicate mixed metal oxide ceramic formed during a high-temperature oxidation process which is then subjected to chemical surface treatment.		
Special Statement on Crystalline Silica	Without dust removal equipment, prolonged agitation of dry powder may generate airborne dust over an 8-hour time weighted average at action levels for respirable crystalline silica. Engineering controls and dust respirators recommended.		
Skin Contact	Dust may irritate skin on prolonged exposure.		
Inhalation	Dust may irritate sinuses, and respiratory system. Chronic exposure above Occupational Exposure Limits increases the risk of developing lung disease.		
Eye Contact	Dust may irritate eyes.		
Toxicological Information for Components (US NIOSH)	Note: Occupational exposure to silica and metal oxides within the solid ceramic spheres does not occur during normal use of Spherix®.		
CMR Effects (carcinogenicity, mutagenicity, and toxicity for reproduction)	Spherix® has not been tested for carcinogenicity, mutagenicity, or toxicity for reproduction. All no studies are known about airborne chronic health effects, specifically associated with cance mutagenicity or toxicity for reproduction from exposure to solid ceramic spheres, the risks associated with any respirable, poorly soluble solids such as these are assumed to potentially		

12. Ecological Information

Ecotoxicity	No data at this time
Mobility	No data at this time

13. Disposal Considerations

Waste Disposal	Cover material to prevent airborne dust and dispose of in a landfill according to state and local
	regulations for non-hazardous waste.

14. Transportation

Not regulated
Not regulated
Not listed

15. Regulatory Information

No



US Regulations						
SARA 302 EHS	Neither Spherix® nor components of the solid ceramic spheres are on the EPCRA Extremely Hazardous Substances list (40 CFR 302).					
SARA 311/312 Classification	Chronic					
SARA 313 Supplier Notification	None					
TSCA	Users are required to conform to air quality and personal protective equipment limits set forth herein.					
California Proposition 65	The following substances are known to the State of California to be carcinogens and/or reproductive toxicants: silica, crystalline.					
State Right to Know						
Component		CAS	MA _{1,2}	NJ _{3,4}	PA ₅	RI ₆
Calcium oxide		1305-78-8	Yes	Yes	Yes	No
Iron oxide		1309-37-1	Yes	Yes	Yes	No
Magnesium oxide		1309-48-4	No	Yes	No	No
Potassium oxide		12136-45-7	No	Yes	No	No
Silica-crystalline (SiO2), quartz		14808-60-78	Yes	Yes	Yes	No

- 1. Massachusetts Department of Public Health, no date
- 2. 189th General Court of The Commonwealth of Massachusetts, no date

1313-59-3

- 3. New Jersey Department of Health and Senior Services, 2010a
- 4. New Jersey Department of Health, 2010b
- 5. Pennsylvania Code, 1986

Sodium Oxide

6. Rhode Island Department of Labor and Training, no date

16. Other Information

Training Instructions	Workers exposed to crystalline silica are required to obtain training to be in compliance with OSHA Final rules for silica (81 FR 16286-16890) published March 26, 2016, which are applicable to the safe handling and use of Spherix® products. Follow company training, housekeeping, air quality engineering controls, and use the proper personal protective equipment described above.
Data Sources	ACGIH® (American Conference of Governmental Industrial Hygienists) New Jersey Right to Know Hazardous Substance Fact Sheets US OSHA, 29 CFR 1910, Tables Z-1, Z-2, Z-3 US Centers for Disease Control and Prevention, NIOSH Pocket Guide
Prepared By	Spherix
Date of Issue	May 2021
Version	5

Notice to Reader

The information provided herein was believed by Spherix Products to be accurate at the time of preparation or prepared from sources believed to be reliable, but it is the responsibility of the user to investigate and understand other pertinent sources of information, to comply with all laws and procedures applicable to the safe handling and use of the product, and to determine the suitability of the product for its intended use. All products supplied by Spherix Products are subject to Spherix Products terms and conditions of sale. SPHERIX PRODUCTS MAKES NO WARRANTY, EXPRESS OR IMPLIED, CONCERNING THE PRODUCT OR THE MERCHANTABILITY OR FITNESS THEREOF FOR ANY PURPOSE OR CONCERNING THE ACCURACY OF ANY INFORMATION PROVIDED BY SPHERIX PRODUCTS except that the product shall conform to Spherix Products specifications. Nothing contained herein constitutes an offer for the sale of any product.